









Multispiral

RYCO Hose Series	Size Inside Diameter	Recommended For	Construction	Performance Specifications Met or Exceeded
H12A AVENGER 	-06 to -32 (3/8" to 2")	Very high pressure hydraulic oil lines.	Synthetic rubber tube. Four wire spirals. Black cover.	SAE 100R12 AS 3791 100R12 EN 856 Type R12 EN 856 Type 4SP (-12 to -32) ISO 3862 Type 6
H12D DIEHARD 	-06 to -32 (3/8" to 2")	Very high pressure hydraulic oil lines. Very high abrasion resistant cover.	Synthetic rubber tube. Four wire spirals. Black cover. Black extra abrasion and oil resistant synthetic rubber cover. "FRAS" Flame resistance and Anti Static.	SAE 100R12 AS 3791 100R12 EN 856 Type R12 EN 856 Type 4SP (-12 to -32) ISO 3862 Type 6
H12S SLIDER 	-06 to -24 (3/8" to 1.1/2")	Very high pressure hydraulic oil lines. Extremely abrasion resistant exterior protection layer.	Synthetic rubber tube. Four wire spirals. Black cover with exterior protection layer.	SAE 100R12 AS 3791 100R12 EN 856 Type R12 EN 856 Type 4SP (-12 to -24) ISO 3862 Type 6
H13A AVENGER 	-12 to -32 (3/4" to 2")	Extremely high pressure hydraulic oil lines.	Synthetic rubber tube. Four or six wire spirals. Black cover.	SAE 100R13 AS 3791 100R13 EN 856 Type R13 ISO 3862 Type 7
H13D DIEHARD 	-12 to -32 (3/4" to 2")	Extremely high pressure hydraulic oil lines. Very high abrasion resistant cover.	Synthetic rubber tube. Four or six wire spirals. Black cover. Black extra abrasion and oil resistant synthetic rubber cover. "FRAS" Flame resistance and Anti Static.	SAE 100R13 AS 3791 100R13 EN 856 Type R13 ISO 3862 Type 7
H13S SLIDER 	-12 to -24 (3/4" to 1.1/2")	Extremely high pressure hydraulic oil lines. Extremely abrasion resistant exterior protection layer.	Synthetic rubber tube. Four or six wire spirals. Black cover with exterior protection layer.	SAE 100R13 AS 3791 100R13 EN 856 Type R13 ISO 3862 Type 7
H15D DIEHARD 	-12 to -24 (3/4" to 1.1/2")	Extremely high pressure hydraulic oil lines. Very high abrasion resistant cover.	Synthetic rubber tube. Four or six wire spirals. Black cover. Black extra abrasion and oil resistant synthetic rubber cover. "FRAS" Flame resistance and Anti Static.	SAE 100R15
HSHA SPIRAL 	-12 to -32 (3/4" to 2")	Extra high pressure hydraulic oil lines.	Synthetic rubber tube. Four wire spirals. Black cover.	EN 856 Type 4SH

HSPA
SPIRAL



-04 to -10
(1/4" to 5/8")

Extra high pressure
hydraulic oil lines.

Synthetic rubber tube.
Four wire spirals.
Black cover.

EN 856 Type 4SP

Items found 1 to 9 of 9

[Top of Page](#)

All rights reserved
©Copyright
Ryco Hydraulics 2006.