







## One Wire Braid

RYCO Hose Series	Size Inside Diameter	Recommended For	Construction	Performance Specifications Met or Exceeded
<b>RQP1</b> SURVIVOR 	-4 to -16 (1/4" to 1")	High temperature, high pressure oil lines; and some phosphate ester fluids.	Synthetic rubber tube. One wire braid. Thin, non-skive blue cover.	SAE 100R1AT AS 3791 100R1AT DIN 20022 - 1SN EN 853 Type 1SN ISO 1436 Type 1AT
<b>RQP5</b> SURVIVOR 	-4 to -32 (3/16" to 1.13/16")	High temperature, medium to high pressure hydraulic oil lines; some phosphate ester fluids.	Synthetic rubber tube. Polyester inner braid, one wire braid. Blue polyester braid cover.	SAE 100R5 SAE J1402 Type All (Up to -12) AS 3791 100R5
<b>T1A</b> AVENGER 	-4 to -32 (1/4" to 2")	High pressure hydraulic oil lines.	Synthetic rubber tube. One wire braid. Thin, non-skive black cover.	SAE 100R1AT AS 3791 100R1AT DIN 20022 - 1SN EN 853 Type 1SN ISO 1436 Type 1AT
<b>T1D</b> DIEHARD 	-4 to -32 (1/4" to 2")	High pressure hydraulic oil lines. Very high abrasion resistant cover.	Synthetic rubber tube. One wire braid. Thin, non-skive black cover. Black extra abrasion and oil resistant synthetic rubber cover. "FRAS" Flame resistance and Anti Static.	SAE 100R1AT AS 3791 100R1AT DIN 20022 - 1SN EN 853 Type 1SN ISO 1436 Type 1AT
<b>T1F</b> AVENGER 	-4 to -12 (1/4" to 3/4")	Fire Suppression Systems.	Synthetic rubber tube. One wire braid. Thin, non-skive red cover resistant to heat and flame.	SAE 100R1AT AS 3791 100R1AT DIN 20022 - 1SN EN 853 Type 1SN ISO 1436 Type 1AT
<b>T5</b> TRUCKER 	-4 to -32 (3/16" to 1.13/16")	Medium to high pressure hydraulic oil lines. Also suitable for fuel lines, airbrake lines, etc.	Synthetic rubber tube. Polyester inner braid, one wire braid. Black polyester braid cover.	SAE 100R5 SAE J1402 Type All (Up to -12) AS 3791 100R5

Items found 1 to 6 of 6